

2222 S Hamilton Street Dalton, Georgia 30721 phone: 800-809-7086 SIGNATUREFLOORING.COM

Real Appeal - L0001

PRODUCT CONSTRUCTION

Construction:Luxury Vinyl TileWear Layer:20 milsOverall Thickness5 MMPlank Size:6" x 48"

Finish: Commercial Urethane Installation: Loose lay / Glue Down Adhesive Signature 3000

PACKAGING

Sq. Ft. per Carton20.00 sq. ft.Pieces per Carton10Weight per Carton:36.4 lbs

PRODUCT TESTING

Impact Sound Conduction / ASTM E492-09

Slip Resistance / ASTM D 2047

Sign Resistance / ASTM D 2047

Sign Resistance / ASTM F2400

Dimensional Stability / ASTM F2199 < .012" /ft
Short Term Indentation / ASTM F1914 Passes
Long Term Indentation / ASTM F970 Passes

Flexibility / ASTM F 137 Passes 6mm Mandrel

Resistance to Heat / ASTM F 1514 Passes
Resistance to Light / ASTM 1515 Passes

Resistance to Chemicals / ASTM F 925 5 min = Passes, 24 hr = Passes Radiant Flux / ASTM 648 5 o.45 watts/cm², NFPA Class I

Smoke Density / ASTM E 662 Flaming Passes, <450

WARRANTIES

Warranty: 10 Year Limited Commercial Wear
Signature 3000 Adhesive must be used, use of any other adhesive will

void the warranty.

SUSTAINABLITY

Indoor Air Quality...FloorScore® Certified