

400Z. SYNTHETIC FIBER CARPET PAD

PRODUCT CONSTRUCTION

WEIGHT:	40 OZ.
THICKNESS:	0.420
DENSITY LBS./CU.FT.	8.9
TENSILE STRENGTH:	
LENGTH	340
WIDTH	354
WEIGHT	3
ROLL WIDTH:	6'/12'
ROLL LENGTH:	60'/60'

PRODUCT TESTING

RADIANT PANEL (ASTM E-648):	CLASS 1
PILL TEST:	PASSES
FHA TYPE/CLASS:	H 1 & 2
R RATING:	2.05

SUSTAINABILITY

RECYCLABLE:	CAN BE 100% RECYCLED
RECYCLED CONTENT:	MANUFACTURED FROM HIGH PERCENTAGE OF INDUSTRY-DERIVED RECYCLED FIBERS (NYLON, POLYESTER, AND POLYPROPYLENE)
VOC/INDOOR AIR QUALITY:	EXCEEDS CRI GREEN LABEL, REGISTRATION CC-851008
REGIONAL MATERIALS:	MADE IN THE USA; DALTON, GA 30720

WARRANTY

WARRANTY:	LIMITED LIFETIME COMMERCIAL WARRANTY
-----------	--------------------------------------

Signature Flooring, warrants that its manufactured product are free from any defects in workmanship and material, will provide satisfactory service and a lively and resilient foundation for the life of the carpet under which it is originally installed. This warranty applies only when properly installed over flat, smooth, hard surfaces on or above grade.

Signature Flooring, as a sole and exclusive remedy, will replace, without charge, any manufactured product, which does not render satisfactory service in normal use F.O.B. manufacturing plant. This warranty does not include the cost of removal or installation. No liability will be assumed for any consequential damage, loss or expense.