

L5500 – Local Connections

PRODUCT CONSTRUCTION

Style Number:	L5500
Construction:	High Performance Stone Polymer Core SPC
Finish:	Commercial Ceramic Urethane
Wear Layer Thickness:	20 mil (0.5mm)
Over Thickness:	5.5mm (includes 1mm attached cushion)
Size:	7.69" x 60"
Bevel Type:	Painted Bevel
Surface Appearance:	Wood Grain
Embossing:	Standard Emboss
Pieces per carton:	9
Sq. Foot per carton:	28.84
Sq. Foot per pallet:	1,586.06
Installation Method:	3L TripleLock System - Floating

TESTING

Classification ASTM F3261:	Class III, Type B (Embossed)
Slip Resistance ASTM D 2047:	Passes
Dimensional Stability ASTM F 2199	≤0.15
Residual Indentation ASTM F 1914	<8.0%, ≤0.1m
Resistance to Heat ASTM F 1514	Passes
Resistance to Light ASTM 1515	<8.0
Resistance to Chemicals ASTM F 925	Passes
Radiant Flux ASTM 648	Passes
Impact Sound Conduction ASTM 492-09 .	IIC 58 - 8" concrete slab, no ceiling
Sound Transmission Class ASTM E90-09	STC 53 - 8" concrete slab, no ceiling
Static Load ASTM F970	No Damage, Passes
Smoke Density ASTM E662	Passes

WARRANTY

15 Year Limited Commercial (20 mil)

SUSTAINABILITY

Indoor Air Quality. FloorScore® Certified

Local Connections is proudly produced in the USA

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This product is manufactured and recommended for floor covering use only. Walk off mats are recommended at building entry ways.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com 01/2023
