# LOMAX B7038 - BROADLOOM

## SPECIFICATIONS

| | |
|---|---|
| Construction | Tufted |
| Pile Fiber | 100% Solution Dyed Nylon |
| Surface Appearance | Level Patterned Cut & Loop |
| Gauge | 1/10 (39.37 rows per 10 cm) |
| Stitches Per Inch | 14 (55.02 per 10 cm) |
| Pile Height | Average - .181" |
| Total Thickness | Approximate 11/32" |
| Tufted Pile Weight | 32 oz. per sq. yd. (1085 g/m2) |
| Dye Method | Solution Dyed |
| Pattern Repeat | 36" x 36" |
| Primary Backing | Woven Polypropylene |
| Secondary Backing | High Performance SBR Latex with Attached Woven Secondary |
| Density | 6,357 |
| Protection | Soil & Stain Release Technology |
| Tufted Width | 12' |
| Adhesive | Signature 2800 Multi-Purpose Latex<br>Signature 1801 Universal Seam Sealer must be used for all installations where seaming is necessary |

## TESTING

| | |
|---|---|
| Radiant Panel (ASTM E 648) | Class 1 (Direct Glue) |
| Smoke Chamber (ASTM E 662) | Less than 450 (Flaming Mode) |
| Methenamine Pill Test (ASTM D-2859) | Passes |
| Electrostatic Propensity (AATCC 134) | Less than 3.5 KV |

## WARRANTY

Limited 10 Year Commercial Wear Warranty

## SUSTAINABILITY

| | |
|---|---|
| Indoor Air Quality | CRI Green Label Plus Certified 2121 |

Made in USA

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This carpet is manufactured and recommended for floor covering use only. As in all quality carpet, colors are subject to dye lot variations. For optimum side match and finished seam appearance, this product should be installed whenever possible, with seams running perpendicular to major external (outside) light sources. The equipment used to manufacture patterned (graphics) carpet may create visible lines in both length and width directions. This characteristic will not always be detectable in small samples and is not considered a manufacturing defect. Chair pads are recommended under office chairs with rollers to preserve appearance retention, avoid premature or accelerated wear, and act as a deterrent toward delamination. Special backing systems are available that do not require chair pads. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature.