

NATURAL INSTINCT 7300 – WPC

SPECIFICATIONS

Construction	High Performance Waterproof Composite Core Non-Ortho Phthalate Construction
Finish	Commercial Urethane with Double UV Coating
Wear Layer Thickness	20 mil (0.5mm)
Overall Thickness	8 mm (includes 1.5 mm attached cushion)
Size	9"W x 60"L
Bevel Type	V Groove Painted
Texture	Embossed In Register (EIR)
Installation	Uniclic® Locking System – Floating; no adhesive
Note: For glue down installations, attached cushion must be removed.	
Sq. Ft. per Carton	29.92 sq. ft.
Sq. Ft. per Pallet	897.6 sq. ft.

PRODUCT TESTING

Impact Sound Conduction / ASTM 492-09 ...	IIC 62
Slip Resistance / ASTM D2047.....	> 0.7 Dry
Dimensional Stability / ASTM F2199	Passes, Less than 0.020"/ft
Residual Indentation / ASTM F1914.....	Passes
Flexibility / ASTM F137	Passes, 50 mm Mandrel
Resistance to Heat / ASTM F1514	Passes
Resistance to Light / ASTM F1515	Passes
Resistance to Chemicals / ASTM F925	5 min. Passes, 24 hr. Passes
Radiant Flux / ASTM E648	>0.45 watts/ cm ² , NFPA Class 1
Smoke Density / ASTM E662	Passes, <450

WARRANTY

10 Year Limited Light Commercial, including Wear, Joint Integrity, Waterproof, Stain and Pet

SUSTAINABILITY

Indoor Air Quality FloorScore® Certified

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This carpet is manufactured and recommended for floor covering use only. As in all quality carpet, colors are subject to dye lot variations. For optimum side match and finished seam appearance, this product should be installed whenever possible, with seams running perpendicular to major external (outside) light sources. The equipment used to manufacture patterned (graphics) carpet may create visible lines in both length and width directions. This characteristic will not always be detectable in small samples and is not considered a manufacturing defect. Chair pads are recommended under office chairs with rollers to preserve appearance retention, avoid premature or accelerated wear, and act as a deterrent toward delamination. Special backing systems are available that do not require chair pads. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com

08/2018



2222 S HAMILTON STREET, DALTON, GA 30721 • SIGNATUREFLOORING.COM