

# NATURAL INSTINCT 7300 – WPC

## SPECIFICATIONS

|                                                                      |                                                                          |
|----------------------------------------------------------------------|--------------------------------------------------------------------------|
| Construction .....                                                   | High Performance Waterproof Composite Core WPC<br>Phthalate Construction |
| Finish .....                                                         | Commercial Urethane with Double UV Coating                               |
| Wear Layer Thickness .....                                           | 20 mil (0.5mm)                                                           |
| Overall Thickness .....                                              | 8 mm (includes 1.5 mm attached cushion)                                  |
| Size .....                                                           | 9"W x 60"L                                                               |
| Bevel Type .....                                                     | V Groove Painted                                                         |
| Texture .....                                                        | Embossed In Register (EIR)                                               |
| Installation .....                                                   | Uniclic® Locking System – Floating                                       |
| Note: For glue down installations, attached cushion must be removed. |                                                                          |
| Sq. Ft. per Carton .....                                             | 29.92 sq. ft.                                                            |
| Sq. Ft. per Pallet .....                                             | 897.6 sq. ft.                                                            |

## PRODUCT TESTING

|                                            |                                |
|--------------------------------------------|--------------------------------|
| Impact Sound Conduction / ASTM E492-09 ... | IIC 62                         |
| Slip Resistance / ASTM D2047.....          | > 0.7 Dry                      |
| Dimensional Stability / ASTM F2199 .....   | Passes, Less than 0.020"/ft    |
| Residual Indentation / ASTM F1914.....     | Passes                         |
| Flexibility / ASTM F137 .....              | Passes, 50 mm Mandrel          |
| Resistance to Heat / ASTM F1514 .....      | Passes                         |
| Resistance to Light / ASTM F1515 .....     | Passes                         |
| Resistance to Chemicals / ASTM F925 .....  | 5 min=Passes, 24 hr=Passes     |
| Radiant Flux / ASTM E648 .....             | >0.45 watts/ cm2, NFPA Class 1 |
| Smoke Density / ASTM E662 .....            | Passes, <450                   |

## WARRANTY

15 Year Limited Commercial

## SUSTAINABILITY

Indoor Air Quality ..... FloorScore® Certified

Made in China

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This product is manufactured and recommended for floor covering use only. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature.

For samples, specifications, or other information please contact your sales representative or visit [signatureflooring.com](http://signatureflooring.com)

07/2026

 **Signature**

2222 S HAMILTON STREET, DALTON, GA 30721 • [SIGNATUREFLOORING.COM](http://SIGNATUREFLOORING.COM)