

NATURE CRAFT 2.5 L1003 – LVT

SPECIFICATIONS

Construction	Luxury Vinyl Tile
Finish	Commercial Urethane with Ceramic Finish
Wear Layer Thickness	20 mil (0.5mm)
Overall Thickness	2.5 mm
Size	7"W x 48"L
Bevel Type	Micro Bevel
Surface Appearance	Wood Grain
Installation	Full Glue Down
Adhesive	Signature 3200 Premium Carpet Tile/ LVT Adhesive Pressure Sensitive Adhesive (PSA)
Pieces per Carton	16
Sq. Ft. per Carton	37.33 sq. ft.
Sq. Ft. per Pallet	2,053.33 sq. ft.

PRODUCT TESTING

Classification ASTM F1700	Class III, Type A (Smooth), Type B (Embossed)
Slip Resistance / ASTM D2047.....	Dry 0.73, Wet 0.89
DCOF / ASTM A326.3.....	0.67
Dimensional Stability / ASTM F2199	0.3
Residual Indentation / ASTM F1914.....	3.7
Resistance to Heat / ASTM F1514	2.59
Resistance to Light / ASTM F1515	2.74
Resistance to Chemicals / ASTM F925	Passes
Radiant Flux / ASTM E648	>0.45 watts/ cm ²
Impact Sound Conduction / ASTM 492-09 ...	Passes
Sound Transmission Class / ASTM E 90-09 ..	Passes
Flexibility / ASTM F137	Passes

WARRANTY

10 Year Limited Commercial

SUSTAINABILITY

Indoor Air Quality	FloorScore® Certified
--------------------------	-----------------------

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This carpet is manufactured and recommended for floor covering use only. As in all quality carpet, colors are subject to dye lot variations. For optimum side match and finished seam appearance, this product should be installed whenever possible, with seams running perpendicular to major external (outside) light sources. The equipment used to manufacture patterned (graphics) carpet may create visible lines in both length and width directions. This characteristic will not always be detectable in small samples and is not considered a manufacturing defect. Chair pads are recommended under office chairs with rollers to preserve appearance retention, avoid premature or accelerated wear, and act as a deterrent toward delamination. Special backing systems are available that do not require chair pads. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com

09/2019

