

NATURE CRAFT 2.5 L1003 – LVT

SPECIFICATIONS

Construction	Luxury Vinyl Tile
Finish	Commercial Urethane with Ceramic Finish
Wear Layer Thickness	20 mil (0.5mm)
Overall Thickness	2.5 mm
Size	7"W x 48"L
Bevel Type	Micro Bevel
Surface Appearance	Wood Grain
Installation	Full Glue Down
Adhesive	Signature 3200 Premium Carpet Tile/ LVT Adhesive Pressure Sensitive Adhesive (PSA)
Pieces per Carton	16
Sq. Ft. per Carton	37.33 sq. ft.
Sq. Ft. per Pallet	2,053.33 sq. ft.

PRODUCT TESTING

Classification ASTM F1700	Class III, Type B, Phthalate Free
Slip Resistance / ASTM D2047	Dry 0.73, Wet 0.89
DCOF / ASTM A326.3	0.67
Dimensional Stability / ASTM F2199	0.3
Residual Indentation / ASTM F1914	3.7
Resistance to Heat / ASTM F1514	2.59
Resistance to Light / ASTM F1515	2.74
Resistance to Chemicals / ASTM F925	Passes
Radiant Flux / ASTM 648	>0.45 watts/ cm ³
Smoke Density ASTM E662	Passes, < 450
Impact Sound Conduction / ASTM 492-09 ...	Passes
Sound Transmission Class / ASTM E 90-09 ..	Passes
Flexibility / ASTM F137	Passes

WARRANTY

15 Year Limited Commercial

SUSTAINABILITY

Indoor Air Quality FloorScore® Certified

Made in China

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This product is manufactured and recommended for floor covering use only. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com

07/2026



2222 S HAMILTON STREET, DALTON, GA 30721 • SIGNATUREFLOORING.COM