

NOTABLE 7400 – WPC

SPECIFICATIONS

Construction	High Performance Waterproof Composite Core WPC Phthalate Free
Finish	Wood Grain
Wear Layer Thickness	20 mil (0.5mm)
Overall Thickness	8 mm (includes 1.5 mm attached cushion)
Size	6"W x 48"L
Bevel Type	Micro Bevel
Texture	Standard Emboss
Installation	Uniclic® Locking System – Floating; no adhesive
Note: For glue down installations, attached cushion must be removed.	
Sq. Ft. per Carton	15.76 sq. ft.
Sq. Ft. per Pallet	1229.28 sq. ft.

PRODUCT TESTING

Impact Sound Conduction / ASTM 492-09 ...	IIC 62
Slip Resistance / ASTM D2047.....	> 0.7 Dry
Dimensional Stability / ASTM F2199	Passes, Less than 0.020"/ft
Residual Indentation / ASTM F1914.....	Passes
Flexibility / ASTM F137	Passes, 50 mm Mandrel
Resistance to Heat / ASTM F1514	Passes
Resistance to Light / ASTM 1515	Passes
Resistance to Chemicals / ASTM F925	.5 min=Passes, 24 hr=Passes
Radiant Flux / ASTM 648	>0.45 watts/ cm2, NFPA Class 1
Smoke Density / ASTM E662	Passes, <450

WARRANTY

15 Year Limited Commercial

Made in China

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This product is manufactured and recommended for floor covering use only. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com

09/2026

 Signature

2222 S HAMILTON STREET, DALTON, GA 30721 • SIGNATUREFLOORING.COM