

## Natural Instinct (7300) – WPC

### PRODUCT CONSTRUCTION

|                       |                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------|
| Construction:         | High Performance Waterproof Composite Core WPC<br>Non-Ortho Phthalate Construction                                      |
| Finish:               | Commercial Urethane with Double UV Coating                                                                              |
| Wear Layer Thickness: | 20 mil (0.50 mm)                                                                                                        |
| Overall Thickness:    | 8 mm (includes 1.5 mm attached cushion)                                                                                 |
| Installation Method:  | Uniclic® Locking System – Floating; no adhesive<br>Note: For glue down installations, attached cushion must be removed. |
| Size:                 | 9"W x 60"L                                                                                                              |
| Bevel:                | V Groove Painted                                                                                                        |
| Texture:              | Embossed In Register (EIR)                                                                                              |
| Sq. Foot per Carton:  | 29.92                                                                                                                   |
| Sq. Foot per Pallet:  | 897.6                                                                                                                   |

### PRODUCT TESTING

|                                         |                                            |
|-----------------------------------------|--------------------------------------------|
| Impact Sound Conduction (ASTM E492-09): | IIC 62                                     |
| Slip Resistance (ASTM D 2047):          | > 0.7 Dry                                  |
| Dimensional Stability (ASTM F 2199):    | Passes, Less than 0.020"/ft.               |
| Residual Indentation (ASTM F 1914):     | Passes                                     |
| Flexibility (ASTM F 137):               | Passes, 50 mm Mandrel                      |
| Resistance to Heat (ASTM F 1514):       | Passes                                     |
| Resistance to Light (ASTM 1515):        | Passes                                     |
| Resistance to Chemicals (ASTM F 925):   | 5 min. Passes, 24 hr. Passes               |
| Radiant Flux (ASTM 648):                | >0.45 watts/cm <sup>2</sup> , NFPA Class 1 |
| Smoke Density (ASTM E 662):             | Passes, < 450                              |

### WARRANTIES

|           |                                                                                                       |
|-----------|-------------------------------------------------------------------------------------------------------|
| Warranty: | Limited 10 Year Light Commercial Warranty, including Wear, Joint Integrity, Waterproof, Stain and Pet |
|-----------|-------------------------------------------------------------------------------------------------------|

### SUSTAINABILITY

|                     |                       |
|---------------------|-----------------------|
| Indoor Air Quality: | FloorScore® Certified |
|---------------------|-----------------------|

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. . As in all quality product, colors are subject to dye lot variations. This product is manufactured and recommended for floor covering use only. Chair pads are required under office chairs with rollers to preserve appearance retention, avoid premature or accelerated wear, and act as a deterrent toward delamination. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature. For samples, specifications, or technical information please contact your sales representative or Signature at 800-809-7086 / signatureflooring.com