

L1002 Nature Craft 2.0, L1003 Nature Craft 2.5

PRODUCT CONSTRUCTION

Style Number:	L1002 12 mil, L1003 20 mil
Construction:	LVT Plank
Finish:	Commercial Urethane with Ceramic Bead Finish
Wear Layer Thickness:	12 mil (0.3mm) and 20 mil (0.5mm)
Over All Thickness:	2 mm (12 mil) and 2.5 mm (20 Mil)
Size:	7'4" x 48"±
Bevel Type:	Micro Bevel
Pieces per carton:	18 (12mil), 16 (20mil)
Sq. Foot per carton:	42 (12mil), 37.33 (20 mil)
Sq. Foot per pallet:	2,520 (12mil), 2,053.33 (20mil)
Cartons per Pallet:	60 (12mil), 55 (20mil)
Installation Method:	Glue Down
Adhesive	Spread adhesiveSignature 3000 Premium Pressure Sensitive Adhesive (PSA)*

TESTING

Classification ASTM F1700	Class III, Type B Phthalate Free
Slip Resistance ASTM D2047	Exceeds Ind. Standards (12 mil) Dry .76, Wet .87 (20 mil) Dry .73, Wet .89
Dimensional Stability ASTM F2199	Passes
Size and Squareness ASTM F2055	Passes
Wearlayer Thickness ASTM 410	Passes
Thickness ASTM F386 11	Passes
Flexibility ASTM F137 08	Passes
Short Term Residual Indentation ASTM F1914	Passes
Long Term Residual Indentation ASTM F970	Passes
Resistance to Heat ASTM F1514	Passes
Resistance to Light ASTM F1515	Passes
Resistance to Chemicals ASTM F925	Passes
Radiant Flux ASTM E648	Passes, meets or exceeds Class 1
Smoke Density ASTM E622	Passes, <450

WARRANTY

10 Year Limited Commercial

SUSTAINABILITY

Indoor Air Quality. FloorScore® Certified

NOTE: For areas with lengths and/or widths longer than 20' the perimeter of the room requires a minimum of a 4" strip of PSA on the perimeter of the subfloor and at 20' distance parallel to the perimeter forming a grid. For commercial traffic or rolling load areas we recommend Signature 3000 (PSA) adhesive-full glue down method

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and /or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This product is manufactured and recommended for floor covering use only. Walk off mats are recommended at building entry ways.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com 1/2025
