

REAL APPEAL L0001 – LOOSE LAY LVT

SPECIFICATIONS

Construction	Luxury Vinyl Tile
Finish	Commercial Urethane with Double UV Coating
Wear Layer	20 mil
Overall Thickness	5 mm
Size	6" x 48"
Bevel Type	Micro Bevel
Installation	Loose Lay with Perimeter Glue or Full Spread Adhesive
Adhesive	Signature 3200 Premium Carpet Tile/LVT Adhesive
Sq. Ft. per Carton	20 sq. ft.
Pieces per Carton	10

PRODUCT TESTING

Slip Resistance / ASTM D 2047.....	> .84 Dry/0.86 Wet
Dimensional Stability / ASTM F2199	Passes
Short Term Indentation / ASTM F1914	Passes
Long Term Indentation / ASTM F970	Passes
Flexibility / ASTM F 137	Passes 6mm Mandrel
Resistance to Heat / ASTM F 1514	Passes
Resistance to Light / ASTM 1515	Passes
Resistance to Chemicals / ASTM F 925	5 min = Passes, 24 hr = Passes
Radiant Flux / ASTM 648	>0.45 watts/cm ² , NFPA Class I
Smoke Density / ASTM E 662 Flaming	Passes, <450

WARRANTY

Limited 15 Year Limited Commercial

Made in China

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This product is manufactured and recommended for floor covering use only. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com

09/2026



2222 S HAMILTON STREET, DALTON, GA 30721 • SIGNATUREFLOORING.COM