

# REAL APPEAL L0001 – LOOSE LAY LVT

## SPECIFICATIONS

Construction .....	Luxury Vinyl Tile
Wear Layer .....	20 mils
Overall Thickness .....	5 MM
Plank Size .....	6" x 48"
Finish .....	Commercial Urethane
Installation .....	Loose Lay / Glue Down
Adhesive .....	Signature 3200 Premium Carpet Tile/LVT Adhesive
Sq. Ft. per Carton .....	20.00 sq. ft.
Pieces per Carton .....	10
Weight per Carton .....	36.4 lbs

## PRODUCT TESTING

Impact Sound Conduction / ASTM E492-09 ....	NA Pending decision 1-07-2019
Slip Resistance / ASTM D 2047.....	> .8
Dimensional Stability / ASTM F2199 .....	< .012" /ft
Short Term Indentation / ASTM F1914 .....	Passes
Long Term Indentation / ASTM F970 .....	Passes
Flexibility / ASTM F 137 .....	Passes 6mm Mandrel
Resistance to Heat / ASTM F 1514 .....	Passes
Resistance to Light / ASTM 1515 .....	Passes
Resistance to Chemicals / ASTM F 925 .....	5 min = Passes, 24 hr = Passes
Radiant Flux / ASTM 648 .....	>0.45 watts/cm <sup>2</sup> , NFPA Class I
Smoke Density / ASTM E 662 Flaming .....	Passes, <450

## WARRANTY

Limited 10 Year Commercial Wear Warranty

Signature 3200 Premium Carpet Tile/LVT Adhesive must be used, use of any other adhesive will void the warranty

## SUSTAINABILITY

Indoor Air Quality .....

FloorScore® Certified

Made in USA

---

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This carpet is manufactured and recommended for floor covering use only. As in all quality carpet, colors are subject to dye lot variations. For optimum side match and finished seam appearance, this product should be installed whenever possible, with seams running perpendicular to major external (outside) light sources. The equipment used to manufacture patterned (graphics) carpet may create visible lines in both length and width directions. This characteristic will not always be detectable in small samples and is not considered a manufacturing defect. Chair pads are recommended under office chairs with rollers to preserve appearance retention, avoid premature or accelerated wear, and act as a deterrent toward delamination. Special backing systems are available that do not require chair pads. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature.