

URBAN ESCAPES L1009 – LOOSE LAY LVT

SPECIFICATIONS

Construction	Loose Lay LVT Plank
Finish	Commercial Urethane with Ceramic Bead Finish
Wear Layer Thickness	20 mil (0.5mm)
Overall Thickness	5 mm
Size	7"W x 48"L
Bevel Type	Micro Bevel
Installation	Loose Lay with perimeter glue or with full
Adhesive	Signature 3200 Premium Carpet Tile/LVT Adhesive Pressure Sensitive Adhesive (PSA)*
Pieces per Carton	8
Sq. Ft. per Carton	18.67 sq. ft.
Sq. Ft. per Pallet	1,026.85 sq. ft.
Cartons per Pallet	55

PRODUCT TESTING

Classification ASTM F1700	Class III, Type B Phthalate Free
Slip Resistance / ASTM D2047.....	Exceed Ind. Standards Wet: 0.5 / Dry: 0.74
DCOF / ASTM A326.3.....	0.65
Dimensional Stability / ASTM F2199	Passes
Size and Squareness / ASTM F2055	Passes
Wearlayer Thickness / ASTM 410	Passes
Thickness / ASTM F386	Passes
Flexibility / ASTM F137	Passes
Residual Indentation / ASTM F1914.....	Passes
Static Load Limit / ASTM F970	Passes
Resistance to Heat / ASTM F1514	Passes
Resistance to Light / ASTM F1515	Passes
Resistance to Chemicals / ASTM F925	Passes
Radiant Flux / ASTM E648	Passes, Meets or Exceeds Class 1
Smoke Density / ASTM E662	Passes, <450
Impact Insulation Class (IIC Rating)	54 – 6" slab, no ceiling
Sound Transmission Class (STC)	53

WARRANTY

10 Year Limited Commercial

SUSTAINABILITY

Indoor Air Quality

FloorScore® Certified

Made in the USA

NOTE: For areas with lengths and/or widths longer than 20' the perimeter of the room requires a minimum of a 4" strip of PSA on the perimeter of the subfloor and at 20' distance parallel to the perimeter forming a grid. For commercial traffic or rolling load areas we recommend Signature 3000 (PSA) adhesive-full glue down method

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This carpet is manufactured and recommended for floor covering use only. As in all quality carpet, colors are subject to dye lot variations. For optimum side match and finished seam appearance, this product should be installed whenever possible, with seams running perpendicular to major external (outside) light sources. The equipment used to manufacture patterned (graphics) carpet may create visible lines in both length and width directions. This characteristic will not always be detectable in small samples and is not considered a manufacturing defect. Chair pads are recommended under office chairs with rollers to preserve appearance retention, avoid premature or accelerated wear, and act as a deterrent toward delamination. Special backing systems are available that do not require chair pads. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com

07/2021

 **Signature**

2222 S HAMILTON STREET, DALTON, GA 30721 • SIGNATUREFLOORING.COM