

URBAN ESCAPES L1011 – SPC

SPECIFICATIONS

Construction	Stone Polymer Core (SPC)
Finish	Commercial Urethane with Polyurethane Finish
Wear Layer Thickness	20 mil (0.5mm)
Overall Thickness	5 mm with 1mm attached underlayment
Size	7"W x 48"L
Bevel Type	Micro Bevel
Installation	Click Floating System
Adhesive	No Adhesive Required
Pieces per Carton	10
Sq. Ft. per Carton	23.64 sq. ft.
Sq. Ft. per Pallet	1,536.6 sq. ft.
Cartons per Pallet	65

PRODUCT TESTING

Classification ASTM F3261	Class III, Type B, Phthalate Free
Slip Resistance / ASTM D2047	Exceeds Industry Standards
DCOF / ASTM A326.3	0.76
Dimensional Stability / ASTM F2199	Passes
Size and Squareness / ASTM F2421	Passes
Wearlayer Thickness / ASTM 410	Passes
Thickness / ASTM F386 11	Passes
Flexibility / ASTM F137 08	Passes
Residual Indentation / ASTM F1914	Passes
Static Load Limit / ASTM F970	Max loading 250 lb per sq inch
Resistance to Heat / ASTM F1514	Passes
Resistance to Light / ASTM F1515	Passes
Resistance to Chemicals / ASTM F925	Passes
Radiant Flux / ASTM E648	Passes, meets or exceeds Class I
Smoke Density / ASTM E662	Passes, <450
Impact Insulation Class (IIC Rating)	72 – 6" slab, drop ceiling
Sound Transmission Class (STC)	71

WARRANTY

15 Year Limited Commercial

SUSTAINABILITY

Indoor Air Quality FloorScore® Certified

Made in the USA

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This product is manufactured and recommended for floor covering use only. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com

07/2026



2222 S HAMILTON STREET, DALTON, GA 30721 • SIGNATUREFLOORING.COM