

# URBAN ESCAPES L1010 – SPC

## SPECIFICATIONS

Construction .....	Stone Polymer Core (SPC)
Finish .....	Commercial Urethane with Polyurethane Finish
Wear Layer Thickness .....	20 mil (0.5mm)
Overall Thickness .....	5 mm with 1mm attached underlayment
Size .....	7"W x 48)L
Bevel Type .....	Micro Bevel
Installation .....	Click Floating System
Adhesive .....	No Adhesive Required
Pieces per Carton .....	10
Sq. Ft. per Carton .....	23.64 sq. ft.
Sq. Ft. per Pallet .....	1,536.6 sq. ft.
Cartons per Pallet .....	65

## PRODUCT TESTING

Classification ASTM F3261 .....	Class III, Type B (Embossed)
Slip Resistance / ASTM D2047 .....	Exceeds Industry Standards
DCOF / ASTM A326.3 .....	0.65
Dimensional Stability / ASTM F2199 .....	Passes
Size and Squareness / ASTM F2421 .....	Passes
Wearlayer Thickness / ASTM 410 .....	Passes
Thickness / ASTM F386 .....	Passes
Flexibility / ASTM F137 .....	Passes
Residual Indentation / ASTM F1914 .....	Passes
Static Load Limit / ASTM F970 .....	Max loading 250 lb per sq inch
Resistance to Heat / ASTM F1514 .....	Passes
Resistance to Light / ASTM F1515 .....	Passes
Resistance to Chemicals / ASTM F925 .....	Passes
Radiant Flux / ASTM E648 .....	Passes, meets or exceeds Class I
Smoke Density / ASTM E662 .....	Passes, <450
Impact Insulation Class (IIC Rating) .....	72 – 6" slab, drop ceiling
Sound Transmission Class (STC) .....	71

## WARRANTY

10 Year Limited Commercial

## SUSTAINABILITY

Indoor Air Quality .....

FloorScore® Certified

Made in the USA

NOTE: For areas with lengths and/or widths longer than 20' the perimeter of the room requires a minimum of a 4" strip of PSA on the perimeter of the subfloor and at 20' distance parallel to the perimeter forming a grid. For commercial traffic or rolling load areas we recommend Signature 3000 (PSA) adhesive-full glue down method

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This carpet is manufactured and recommended for floor covering use only. As in all quality carpet, colors are subject to dye lot variations. For optimum side match and finished seam appearance, this product should be installed whenever possible, with seams running perpendicular to major external (outside) light sources. The equipment used to manufacture patterned (graphics) carpet may create visible lines in both length and width directions. This characteristic will not always be detectable in small samples and is not considered a manufacturing defect. Chair pads are recommended under office chairs with rollers to preserve appearance retention, avoid premature or accelerated wear, and act as a deterrent toward delamination. Special backing systems are available that do not require chair pads. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature.

For samples, specifications, or other information please contact your sales representative or visit [signatureflooring.com](http://signatureflooring.com)

07/2021



2222 S HAMILTON STREET, DALTON, GA 30721 • SIGNATUREFLOORING.COM