

URBAN ESCAPES L1011 – SPC

SPECIFICATIONS

| | |
|----------------------|--|
| Construction | Stone Polymer Core (SPC) |
| Finish | Commercial Urethane with Polyurethane Finish |
| Wear Layer Thickness | 20 mil (0.5mm) |
| Overall Thickness | 5 mm with 1mm attached underlayment |
| Size | 7"W x 48"L |
| Bevel Type | Micro Bevel |
| Installation | Click Floating System |
| Adhesive | No Adhesive Required |
| Pieces per Carton | 10 |
| Sq. Ft. per Carton | 23.64 sq. ft. |
| Sq. Ft. per Pallet | 1,536.6 sq. ft. |
| Cartons per Pallet | 65 |

PRODUCT TESTING

| | |
|--------------------------------------|----------------------------------|
| Classification ASTM F3261 | Class III, Type B (Embossed) |
| Slip Resistance / ASTM D2047 | Exceeds Industry Standards |
| DCOF / ASTM A326.3 | 0.76 |
| Dimensional Stability / ASTM F2199 | Passes |
| Size and Squareness / ASTM F2421 | Passes |
| Wearlayer Thickness / ASTM 410 | Passes |
| Thickness / ASTM F386 | Passes |
| Flexibility / ASTM F137 | Passes |
| Residual Indentation / ASTM F1914 | Passes |
| Static Load Limit / ASTM F970 | Max loading 250 lb per sq inch |
| Resistance to Heat / ASTM F1514 | Passes |
| Resistance to Light / ASTM F1515 | Passes |
| Resistance to Chemicals / ASTM F925 | Passes |
| Radiant Flux / ASTM E648 | Passes, meets or exceeds Class I |
| Smoke Density / ASTM E662 | Passes, <450 |
| Impact Insulation Class (IIC Rating) | 72 – 6" slab, drop ceiling |
| Sound Transmission Class (STC) | 71 |

WARRANTY

10 Year Limited Commercial

SUSTAINABILITY

Indoor Air Quality FloorScore® Certified

Made in the USA

NOTE: For areas with lengths and/or widths longer than 20' the perimeter of the room requires a minimum of a 4" strip of PSA on the perimeter of the subfloor and at 20' distance parallel to the perimeter forming a grid. For commercial traffic or rolling load areas we recommend Signature 3000 (PSA) adhesive-full glue down method

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This carpet is manufactured and recommended for floor covering use only. As in all quality carpet, colors are subject to dye lot variations. For optimum side match and finished seam appearance, this product should be installed whenever possible, with seams running perpendicular to major external (outside) light sources. The equipment used to manufacture patterned (graphics) carpet may create visible lines in both length and width directions. This characteristic will not always be detectable in small samples and is not considered a manufacturing defect. Chair pads are recommended under office chairs with rollers to preserve appearance retention, avoid premature or accelerated wear, and act as a deterrent toward delamination. Special backing systems are available that do not require chair pads. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com

05/2026



2222 S HAMILTON STREET, DALTON, GA 30721 • SIGNATUREFLOORING.COM