



2222 S Hamilton Street phone: 800-809-7086
Dalton, Georgia 30721 SIGNATUREFLOORING.COM

L1011 –Urban Escapes SPC Floating

PRODUCT CONSTRUCTION

Style Number:	L1011
Construction:	Stone Polymer Core (SPC)
Finish:	Commercial Urethane with Polyurethane Finish
Wear Layer Thickness:	20 mil (0.5mm)
Over Thickness:	5 mm with 1mm attached underlayment
Size:	7"W x 48"L
Bevel Type:	Micro Bevel
Pieces per carton:	10
Sq. Foot per carton:	23.64 sf
Sq. Foot per pallet:	1,536.6 sf
Cartons per Pallet:	65
Installation Method:	Click Floating System
Adhesive	No Adhesive Required

TESTING

Classification ASTM F3261	Class III, Type B (Embossed)
Slip Resistance ASTM D2047	Exceeds industry Standards
Dimensional Stability ASTM F2199	Passes
Size and Squareness ASTM F2421	Passes
Wearlayer Thickness ASTM 410	Passes
Thickness ASTM F386	Passes
Flexibility ASTM F137	Passes
Residual Indentation ASTM F1914	Passes
Static Load ASTM F970	Max loading 250 lb per sq inch
Resistance to Heat ASTM F1514	Passes
Resistance to Light ASTM F1515	Passes
Resistance to Chemicals ASTM F925	Passes
Radiant Flux ASTM E648	Passes, meets or exceeds Class I
Smoke Density ASTM E662	Passes, <450
Impact Insulation Class (IIC Rating)	72 - 6" slab, drop ceiling
Sound Transmission Class (STC)	71

WARRANTY

10 Year Limited Commercial

SUSTAINABILITY

Indoor Air Quality. FloorScore® Certified

NOTE: For areas with lengths and/or widths longer than 20' the perimeter of the room requires a minimum of a 4" strip of PSA on the perimeter of the subfloor and at 20' distance parallel to the perimeter forming a grid. For commercial traffic or rolling load areas we recommend Signature 3000 (PSA) adhesive-full glue down method

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and /or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This product is manufactured and recommended for floor covering use only. Walk off mats are recommended at building entry ways.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com 7/2021
