

VISTA II SG506 – SPC

SPECIFICATIONS

Construction	High Performance Rigid Stone Polymer Core (SPC)
Finish	Commercial Urethane with Polyurethane Finish
Wear Layer Thickness	20 mil (0.50mm)
Overall Thickness	5 mm with 1 mm attached cushion
Size	7"W x 60"L
Edge Profile	Micro Bevel
Pieces per Carton	8
Sq. Ft. per Carton	23.62 sq. ft.
Sq. Ft. per Pallet	1,299.1 sq. ft.
Cartons per Pallet	65

PRODUCT TESTING

Classification ASTM F3261	Class III, Type B (Embossed)
Static Coefficient of Friction / ASTM C1028 ...	0.68 Wet, 0.77 Dry
DCOF / ASTM A326.3	0.70
Dimensional Stability ASTM F2199	Passes
ISO 24337/Size & Squareness, Flatness....	Passes
Wearlayer Thickness ASTM 410	Passes
Thickness / ASTM F387	Passes
Residual Indentation / ASTM F1914.....	Passes
Static Load Limit / ASTM F970	Max loading 250 lb per sq. inch
Resistance to Heat /ASTM F1514	Passes
Resistance to Light / ASTM F1515	Passes
Resistance to Chemicals / ASTM F925	Passes
Radiant Flux / ASTM E648	Passes, meets or exceeds Class 1
Smoke Density / ASTM E662	Passes
Impact Insulation Class (IIC Rating).	69 - 6' slab, drop ceiling
Sound Transmission Class(STC)	61
HIIC Rating / ASTM 32222-20	75

WARRANTY

15 Year Limited Commercial

SUSTAINABILITY

CDPDH/EHLB Standard Method V1.2

(California Specification 01350)Assure Certified

UL2818-2013 Gold Standard for Chemical Emissions for Building

Materials, Finishes, and Furnishings Greenguard Gold Standard Product Certified for Low Chemical Emissions

Made in the USA

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and /or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This product is manufactured and recommended for interior floor covering use only. Walk off mats are recommended at building entry ways.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com

07/2026

 **Signature**

2222 S HAMILTON STREET, DALTON, GA 30721 • SIGNATUREFLOORING.COM