



Signature



VISTA II



Signature



Vista II is inspired by the quiet grandeur of expansive views and untouched natural landscapes, translating the serenity of the outdoors into refined modern interiors. Designed through a biophilic lens, this rigid core collection supports a deeper connection to nature by evoking the openness, balance, texture, and restorative calm of the natural world. Organic warmth and clean contemporary sophistication come together in a collection created to bring natural beauty, visual comfort, and lasting relevance to commercial spaces.

Influenced by the timeless character of weathered wood, **Vista II** showcases a rich, nature-inspired palette with subtle depth, movement, and variation. From the moody tones of shaded woodlands to the lighter warmth of sunlit clearings, each plank is thoughtfully designed to convey texture, authenticity, and a natural sense of place.

Engineered with durable rigid core construction, **Vista II** delivers the performance required for dynamic commercial environments, with resistance to water, stains, scratches, and scuffs. Ideal for hospitality, senior living, retail, multifamily, and other commercial spaces, **Vista II** offers lasting function with a refined aesthetic that feels natural, sophisticated, and enduring.



- High Performance Rigid Stone Polymer Core (SPC)
- Available in 7"W x 60"L plank size
- Micro-bevel profile
- 5mm overall thickness (includes 1mm attached cushion)
- 20 mil wear layer
- Commercial Urethane with Polyurethane Finish
- Water, stain, scratch and scuff resistant
- Inherit thickness promotes acoustical benefits and comfort underfoot
- Twice as thick as traditional LVT for seamless transition to Signature's carpet tile products
- Low maintenance
- Immediate occupancy
- FloorScore Certified
- Made In the USA
- Limited 15 Year Commercial Warranty



VISTA II | 6130 VIANNA | 7"W X 60"L PLANK
RENDEZVOUS LANDSCAPES | SG006 WAVE | 1507 STONE | BROADLOOM 12' W

SIGNATUREFLOORING.COM





VISTA II | 2740 ORSON | 7"W X 60"L PLANK

[SIGNATUREFLOORING.COM](https://signatureflooring.com)



VISTA II | 6130 VIANNA | 7"W X 60"L PLANK

[SIGNATUREFLOORING.COM](https://signatureflooring.com)



VISTA II | 5460 FALLON | 7"W X 60"L PLANK
SIENNA SUMMIT | SG054 | 12' BROADLOOM

SIGNATUREFLOORING.COM





VISTA II | 1750 CAMDEN | 7"W X 60"L PLANK
SIENNA SUMMIT | SG049 | 15' BROADLOOM

SIGNATUREFLOORING.COM



VISTA II | 5710 BRISTOL | 7"W X 60"L PLANK



VISTA II | 3230 EVERLY | 7"W X 60"L PLANK
JOURNEY | TOUR B7019 | 7502 SAFARI

SIGNATUREFLOORING.COM



VISTA II | 9120 WALLIS | 7"W X 60"L PLANK

CROSSROADS | MADRAS S4020 | 1804 TOBACCO | 24" x 24" CARPET TILE | ASHLAR HORIZONTAL




VISTA II | 5680 LACHLAN | 7"W X 60"L PLANK

VISTA II COLORWAYS


Vista II is available in 7" x 60" plank size.




1750 CAMDEN




2740 ORSON




3230 EVERLY




5460 FALLON




5680 LACHLAN



5710 BRISTOL



6130 VIANNA



9120 WALLIS

SPECIFICATIONS

Construction	High Performance Rigid Stone Polymer Core (SPC)
Finish.....	Commercial Urethane with Polyurethane Finish
Wear Layer Thickness	20 mil (0.50 mm)
Overall Thickness.....	5 mm with 1mm attached cushion
Size	7"W x 60"L
Edge Profile	Micro Bevel
Installation	Click Floating System
Adhesive	No Adhesive Required
Pieces per Carton	8
Sq. Ft. per Carton.....	23.62 sq. ft.
Sq. Ft. per Pallet	1,299.1 sq. ft.
Cartons per Pallet	65

PRODUCT TESTING

Classification ASTM F3261	Class III, Type B (Embossed)
Static Coefficient of Friction / ASTM C1028 ...	0.68 Wet, 0.77 Dry
DCOF / ASTM A326.3	0.70
Dimensional Stability / ASTM F2199	Passes
ISO 24337 / Size & Squareness, Flatness	Passes
Wearlayer Thickness / ASTM 410	Passes
Thickness / ASTM F387	Passes
Residual Indentation / ASTM F1914	Passes
Static Load Limit / ASTM F970.	Max loading 250 lb per sq. inch
Resistance to Heat / ASTM F1514	Passes
Resistance to Light / ASTM F1515	Passes
Resistance to Chemicals / ASTM F925	Passes
Radiant Flux / ASTM E648	Passes, meets or exceeds Class I
Smoke Density / ASTM E662	Passes, <450
Impact Insulation Class (IIC Rating)	69 - 6' slab, drop ceiling
Sounds Transmission Class (STC).....	61
HIIC Rating / ASTM 3222-20	75

WARRANTY 15 Year Limited Commercial

SUSTAINABILITY

Indoor Air Quality	FloorScore® Certified
CDPDH/EHLB Standard Method V1.2	
(California Specification 01350).....	Assure Certified
UL2818-2013 Gold Standard for Chemical Emissions for Building	
Materials, Finishes and Furnishings	Greenguard Gold Standard Product Certified for Low Chemical Emissions
Made in USA 	

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This product is manufactured and recommended for interior floor covering use only. Walk off mats are recommended at building entry ways.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com

05/2026



2222 S HAMILTON STREET, DALTON, GA 30721 • SIGNATUREFLOORING.COM