

TERRANE TERRN

SPECIFICATIONS

| | |
|----------------------------------|---|
| Construction | Nonwoven Needlefelt |
| Pile Fiber | Nonpattern Plush |
| Surface Appearance | Solid Loop |
| Pile Height | .3/16" |
| Surface Appearance | .3/8" |
| Pile Height | 30 oz. per sq. yd. |
| Total Thickness | 60 oz. per sq yd. |
| Edging Options | Rubber Edging Border - available in Black or Dark Brown, ADA Approved |
| Width | 13'2" or custom sizes available, along with custom logos, inserts, and borders, No minimum / No Maximum |
| Backing | DB Duo Gel Backing with Non-Skid Quad Back with Non-Skid is used for custom logo rugs |
| Adhesive | Signature 3000 Premium Pressure Sensitive |
| Semipermanent Installation | For semipermanent installed entrance system must be at least 10ft. in length and maintain on a weakly basis |

TESTING

| | |
|---|--|
| Dimensional Stability (ASTM D7570-09) | <0.3 dimensional change |
| Electrostatic Propensity (EN1815) | <0.2 kV (<0.3 kV Quad Back) |
| Electrostatic Resistance (ASTM F150) | Pass, for R.H. ≥ 50% |
| Smoke Density (ASTM E662) | Pass, 241 Flaming; 429 Non-Flaming (Duo Gel) Pass, 437 Flaming; 512 Non-Flaming (Quad Back) |
| Surface Flammability (ASTM D2859) | Pass |

COLOR FASTNESS

| | |
|--------------------------------|--|
| To Light (ISO 105 B02) | 5 |
| To Water (ISO 105 E01) | 5 |
| To Shampoo (ISO 105 C06) | 5 |
| To Rubbing (ISO 105 X12) | 2.5 (Dry), 4 (Wet) (Duo Gel), 2 (Dry), 3 (Wet) (Quad Back) |

WARRANTIES

Limited 5 Year Commercial Warranty

SUSTAINABILITY

| | |
|------------------------|-----|
| Recycled Content | N/A |
|------------------------|-----|

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This carpet is manufactured and recommended for floor covering use only. As in all quality carpet, colors are subject to dye lot variations. For optimum side match and finished seam appearance, this product should be installed whenever possible, with seams running perpendicular to major external (outside) light sources. The equipment used to manufacture patterned (graphics) carpet may create visible lines in both length and width directions. This characteristic will not always be detectable in small samples and is not considered a manufacturing defect. Chair pads are recommended under office chairs with rollers to preserve appearance retention, avoid premature or accelerated wear, and act as a deterrent toward delamination. Special backing systems are available that do not require chair pads. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature.

NOTE: This product contains a high luster yarn which utilizes cut/sheared processing in the design. The luster level of this yarn may cause a directional effect when viewing the pattern.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com

09/2025

