

TRELLIS II TRELL2

SPECIFICATIONS

Construction	Nonwoven Needlefelt
Pile Fiber	Solid colors: 100% Polypropylene Tweed Colors: 80% Polypropylene, 20% Polyester
Surface Appearance	Multi-Level Patterned Loop
Pile Height	3/16"
Surface Appearance	3/8"
Pile Height	37 oz. per sq. yd.
Total Thickness	59 oz. per sq. yd.
Edging Options	Rubber Edging Border - available in Black or Dark Brown, ADA Approved
Width	13'2" or custom sizes available, along with custom logos, inserts, and borders, No minimum / No Maximum
Backing	DB Duo Gel Backing with Non-Skid Quad Back with Non-Skid is used for custom logo rugs
Adhesive	Signature 3000 Premium Pressure Sensitive
Semipermanent Installation	For semipermanent installed entrance system must be at least 10ft. in length and maintain on a weakly basis

TESTING

Dimensional Stability (ASTM D7570-09)	<0.3 dimensional change
Electrostatic Propensity (EN1815)	<0.2 kV
Electrostatic Resistance (ASTM F150)	Pass, for R.H. ≥ 50%
Smoke Density (ASTM E662)	Pass, 253 Flaming; 447 Non-Flaming (Duo Gel) Pass, 469 Flaming; 491 Non-Flaming (Quad Back)
Surface Flammability (ASTM D2859)	Pass

COLOR FASTNESS

To Light (ISO 105 B02)	5
To Water (ISO 105 E01)	5
To Shampoo (ISO 105 C06)	5
To Rubbing (ISO 105 X12)	4 (Dry), 4 (Wet) (Duo Gel), 2 (Dry), 2.5 (Wet) (Quad Back)

WARRANTIES

Limited 5 Year Commercial Warranty

SUSTAINABILITY

Recycled Content	25% pre-consumer recycled content
------------------------	-----------------------------------

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This carpet is manufactured and recommended for floor covering use only. As in all quality carpet, colors are subject to dye lot variations. For optimum side match and finished seam appearance, this product should be installed whenever possible, with seams running perpendicular to major external (outside) light sources. The equipment used to manufacture patterned (graphics) carpet may create visible lines in both length and width directions. This characteristic will not always be detectable in small samples and is not considered a manufacturing defect. Chair pads are recommended under office chairs with rollers to preserve appearance retention, avoid premature or accelerated wear, and act as a deterrent toward delamination. Special backing systems are available that do not require chair pads. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature.

NOTE: This product contains a high luster yarn which utilizes cut/sheared processing in the design. The luster level of this yarn may cause a directional effect when viewing the pattern.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com

09/2025



2222 S HAMILTON STREET, DALTON, GA 30721 • SIGNATUREFLOORING.COM