



Mhisper A BREATH OF STILLNESS

In a world that moves quickly, Whisper offers a gentle pause—a quiet moment drawn from nature's most delicate rhythms. Inspired by the graceful sway of tall grasses, the weightless drift of dandelion seeds, and the soothing pull of the wind across an open landscape, this pattern captures the poetry of movement without motion.

With soft, neutral earth tones that echo sand, stone, and sunlit fields, Whisper invites calm into hospitality spaces. Its subtle texture and linear flow create a grounded elegance—softening interiors and enveloping guests in an atmosphere of ease and serenity.







Designed specifically for guest rooms, Whisper introduces a sense of calm through tonal color and gentle directionality—bringing quiet structure and natural softness to the space. With refined simplicity and understated elegance, it transforms the guest experience, creating a restful retreat that feels both timeless and effortlessly serene.

Let Whisper carry your design forward—with quiet beauty and a breath of nature's own grace.

COVER: WHISPER SG038 | 1502 HUM | BROADLOOM 12' W OR 15'W | PATTERN REPEAT 36" W X 36" L



WHISPER SG038 | 2809 MURMUR | BROADLOOM 12' W OR 15'W | PATTERN REPEAT 36" W X 36" L





WHISPER SG038 | 1803 RUMOR | BROADLOOM 12' W OR 15'W | PATTERN REPEAT 36" W X 36" L



COLORWAYS







1301 SIGH



1502 HUM



1803 RUMOR



2809 MURMUR



3405 SERENE



4706 TRILL



8204 GOSSIP



8607 ECHO

WHISPER SG038

SPECIFICATIONS

Construction Tufted Infinity

Pile Fiber100% Solution Dyed NylonSurface AppearanceLevel Patterned Cut & LoopGauge1/10 (39.37 rows per 10 cm)

Pile HeightAverage - .199Total ThicknessApproximate 10/32"

Dye Method Solution Dyed

Primary Backing Woven Polypropylene

Secondary Backing High Performance SBR Latex with Attached Woven Secondary

Density 5,795

Tufted Width...... 12' / 15'

Adhesive Signature 2800 Multi-Purpose Latex

Signature 1801 Universal Seam Sealer must be used for all installations

where seaming is necessary

TESTING

Radiant Panel (ASTM E 648) Class 1 (Direct Glue)

Smoke Chamber (ASTM E 662) Less than 450 (Flaming Mode)

Methenamine Pill Test (ASTM D-2859) Passes

Electrostatic Propensity (AATCC 134)..... Less than 3.0 KV

WARRANTY

Limited 10 Year Commercial Wear Warranty

SUSTAINABILITY

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and / or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This carpet is manufactured and recommended for floor covering use only. As in all quality carpet, colors are subject to dye lot variations. For optimum side match and finished seam appearance, this product should be installed whenever possible, with seams running perpendicular to major external (outside) light sources. The equipment used to manufacture patterned (graphics) carpet may create visible lines in both length and width directions. This characteristic will not always be detectable in small samples and is not considered a manufacturing defect. Chair pads are recommended under office chairs with rollers to preserve appearance retention, avoid premature or accelerated wear, and act as a deterrent toward delamination. Special backing systems are available that do not require chair pads. Walk off mats are recommended at building entry ways to reduce soiling. For Warranties to apply, all adhesives and seam sealers must be approved by Signature.

NOTE: This product contains a high luster yarn which utilizes cut/sheared processing in the design. The luster level of this yarn may cause a directional effect when viewing the pattern.

For samples, specifications, or other information please contact your sales representative or visit signatureflooring.com

09/2025



GLUE DOWN