

# STONESET L1013 – COMMERCIAL LVT

## SPECIFICATIONS

Construction .....	Commercial LVT
Finish .....	Commercial Reinforced. Ceramic Coating
Wear Layer Thickness .....	20 mil (0.50mm)
Overall Thickness .....	5 mm (0.197mm)
Size .....	18"W x 36"L
Edge Profile .....	Square
Installation .....	Direct Glue Down
Adhesive .....	Signature 3200 Adhesive or 3100 High Moisture Adhesive
Pieces per Carton .....	6
Sq. Ft. per Carton .....	22.84 sq. ft.
Sq. Ft. per Pallet .....	1,461.76 sq. ft.
Cartons per Pallet .....	64

## PRODUCT TESTING

Classification ASTM F1700 .....	Class III, Type B Embossed (Phthalate Free)
Slip Resistance ASTM D2047.....	Exceed Ind. Standards Wet: 0.7 / Dry: 0.6
Dynamic Coefficient of Friction ASTM A326.3.	0.79
Dimensional Stability ASTM F2199 .....	Passes
Size and Squareness ASTM F2055 .....	Passes
Wearlayer Thickness ASTM 410 .....	Passes
Thickness ASTM F386 11 .....	Passes
Flexibility ASTM F137 08 .....	Passes
Residual Indentation ASTM F970.....	Passes, modified 1000psi
Resistance to Heat ASTM F1514 .....	Passes, $\Delta E \leq 8$
Resistance to Light ASTM F1515 .....	Passes, $\Delta E \leq 8$
Resistance to Chemicals ASTM F925 .....	Passes, no change or slight change
Critical Radiant Flux ASTM 648 .....	Passes, $\geq 45$ watts/cm <sup>2</sup> , Class I
Smoke Density ASTM E662 (Flaming) .....	Passes
Smoke Density ASTM E662 (Non-Flaming)..	Passes
Impact Insulation Class (IIC Rating) .....	72 - 6" slab, drop ceiling

## WARRANTY

10 Year Limited Commercial

## SUSTAINABILITY

Indoor Air Quality .....

FloorScore® Certified

NOTE: For areas with lengths and/or widths longer than 20' the perimeter of the room requires a minimum of a 4" strip of PSA on the perimeter of the subfloor and at 20' distance parallel to the perimeter forming a grid. For commercial traffic or rolling load areas we recommend Signature 3000 (PSA) adhesive-full glue down method

Made in the USA

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and /or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance. This product is manufactured and recommended for floor covering use only. Walk off mats are recommended at building entry ways.

For samples, specifications, or other information please contact your sales representative or visit [signatureflooring.com](http://signatureflooring.com)

02/2026



2222 S HAMILTON STREET, DALTON, GA 30721 • SIGNATUREFLOORING.COM